USER MANUAL

OLIGHT

Ostation X

SPECIFICATIONS

Table 1:
Ostation X Kit

Battery Size & Type	46 x 96 mm
Storage/Pump Compartment Capacity (No. of Batteries)	2
No. of Batteries Charged at Same Time	1 or 2 (Individual Charging)
Power Source	USB-C PD
USB-C Input	12V / 3.3A
USB-A Output	5V / 1.5A / 12V / 1.5A
Battery Charge Package	1 pcs
Charge Mode	Standard Charging Mode (Default), Fast Charging Mode
Select Charging Mode	Select the charging mode in the APP
Charging Time	Standard Charging Mode: Approx. 2.5 hrs(Fully charged), Fast Charging Mode: Approx.0.5hrs(Fully charged) Approx. 2.5 hrs per 2 batteries
Body Material	PC, ABS
Dimensions	2.36 x 1.89 x 1.22 in (60 x 48 x 31 mm)
Weight	3.3 lb (1.5 kg)
Package Contents	1 x Ostation X Kit, 1 x USB-C to USB-C Cable, 1 x ACDC Adapter

* All the data is measured under Olight lab. Specifications may slightly differ due to different testing environments and other factors. Please refer to the product in Ostation X Mini page on the Olight Shop.

Scan with the Ostation X Mini product page on the Olight Shop to view the specifications.

Table 2:
USB-C to USB-C Cable

Cable Length	4.92 ft (1.5 m)
Rated Current	3A

PRODUCT OVERVIEW

Figure 1

Figure 2



Figure 4
Loading Batteries & Charging Mode


1
2
or
Bent 30 seconds
Bent 30 seconds
Charging Mode
Fast mode
Slow mode
Fast Charge Indicator
Fully Charged
Fast Charge Indicator
Fully Charged
Fast Charge Indicator
Fully Charged